

# KEM PROOF EWC

**Elastomeric Waterproof Coating with bituminous based**

## DESCRIPTION

KEM Proof EWC is a heavy duty bituminous elastomeric waterproof coating for AC Sheet, roofs and underground structures.

## ADVANTAGES

- Single pack system.
- Easy to applicable or easily brushable.
- Excellent chemical Resistance.
- Good waterproofing Characteristics.
- Cold applied, user friendly.
- Fast drying, ready to use from pack with sufficient open time. Non flammable.

## APPLICATION

All the surfaces must be clean, dry and free from all loosely adhering particles. The prepared surface must be thoroughly wetted with water for absorption and excess water to be removed from the surface. No primer is required for coating Kem Proof EWC.

Apply at least two coats by brush or roller or air spray and allowing 24 hours between each coat. Can be applied by Brush or Roller or Spray.

## CLEANING

All tools must be washed with water immediately after use.

1. Asbestos cement roofs and around 'J' hooks.
2. Sunken portion of toilet.
3. Sewage pipes.
4. Plinth, foundation, basement etc.

## TECHNICAL DATA

- Appearance : Black
- Substrate to be applied : Concrete or Steel
- Drying Time : Touch Dry 2 hrs.
- Coverage : 15 - 20 sq.ft / kg for 2 coats..
- Thickness : 200 to 250 microns DFT depends on the of substrate.

PACKING	STORAGE	SHELF LIFE
1 Kg, 4 Kg, 20 Kg.	Away from moisture & heat	12 Months.

This information is based on our current level of knowledge. It is given in a good faith but it is not intended to guarantee any particular properties. The users must satisfy themselves that there are no circumstances requiring additional information or precautions or the verification of details given herein.

**Chembond Chemicals Limited**, Chembond Centre, EL-71, MIDC, Mahape, Navi Mumbai 400 710.

Tel: 022 2761 8799, 6614 3000 • Fax: 022 2768 1294 • E-mail: chembond@vsnl.com • www.chembondconschem.com